



**TEKNİK ÖZELLİKLER VE
STANDART DONANIM**

- » Çalışma Hizi : 6 m/dak
- » Kapasite : 1.2 mm galvanizli sac
- » Tahrif Sistemi : Redüktör motor tahraklı
- » Motor Gücü : 2.2 kW
- » Ölçüler (UxGxY) : 1300 x 800 x 1100 mm
- » Ağırlık : 465 kg

**TECHNICAL SPECIFICATIONS AND
STANDARD ACCESSORIES**

- » Working Speed : 6 m/min
- » Capacity : 1.2 mm galvanised sheet
- » Power System : with Gearbox
- » Motor power : 2.2 kW
- » Dimensions (LxWxH) : 1300x800x1100 mm
- » Weight : 465 kg

K: Kenet
Pittsburg lock

S: Sürgü
Drive cleat

C: Çerçeve
Power flange

D: Dirsek
Round right cleat

ZS: Z sürgü
Z cleat

G: Gönye
Right angle

BK: Boru keneti
Seam cleat

DBK : Düz Boru Keneti
Flat seam cleat

DS: Düz sürgü
Flat cleat

MODEL		MAX. KAPASITE MAX. CAPACITY	EKM 12			
EKM12 4.0	K-S-C-D	0.5 / 1.2				
EKM12 4.1	K-S-BK-D	0.5 / 1.2				
EKM12 3.3	K-ZS-G	0.5 / 1.2				
EKM12 4.3	K-DBK-DS-D	0.5 / 1.2				

