

# D/LG/KIR/N



## INVERSYS PLUS SERIES -ROTARY SCREW AIR COMPRESSORS



### STANDARD EQUIPMENT

High quality components such as IP55 electric motors with the IE3 efficiency class, IP54 fan motors, star-delta motor starter system, electrical materials selected according to IEC, UL/cUL, CE standards as per the market requirements, high-efficiency screw blocks consuming less energy are provided as standard in all our products.



### SERVICEABILITY

Service-friendly design implemented using a layout that provides instant access to all consumable items, with quick-release protective covers and easy-to-use controllers minimizes downtime and reduces maintenance costs.



## ELECTRONIC CONTROL

Dalgakiran rotary screw compressors are equipped with easy-to-use, robust and long-lasting microprocessor controllers with communication capabilities as per the product line to ensure smooth operation and uninterrupted production.



## SCREW BLOCK

Patented and durable screw block that provides high-capacity of air, and that is specially selected for each model's capacity requirement

Production of air with less loss of air, thanks to the new rotor profiles, and lower torque requirements

New generation bearing design with increased load carrying capabilities



## AIR OIL SEPARATOR

Spin-on or immersed type separator design depending on the product line

### Immersed type separator

High performance separation with three-stage design

More efficient separation at lower volume with deeply wrapped, intertwined separation layers

Low amount of oil mist in outlet air  $\leq 3$  ppm

### Spin-on separator

Easy replacement, ease of assembly and disassembly

Design that does not require a separator tank



## MAIN MOTOR AND DRIVE SYSTEM

High efficiency 400V/3 phase/50Hz, IE3 IP55 electric motors with F Class insulation

Star delta motor starting system

Easy of assembly and disassembly with bush pulleys on belt-pulley models

Direct coupled, long-lasting and efficient transfer system thanks to use of elastic couplings





## INVERSYS PLUS SERIES Rotary Screw Air Compressors

DALGAKIRAN INVERSYS PLUS series variable-speed compressors drive the motor with the frequency converter to adjust the compressor operation speed according to your requirements and save up to 35% energy. Thanks to its high-quality equipment and excellent engineering in its design, it provides a very efficient and flexible use as per requirements. Responds to all requirements between 5.5 and 315 KW.



### ADVANTAGES

- Up to 35% energy saving\*
- Operation at constant output pressure value
- Wide operating pressure range (5-14 bars)
- Soft-starting
- Protection against the adverse effects of peak currents
- Effective production of pressurized air even in case of highly variable pressurized air requirements

\*When compared with compressors without an inverter for business with variable requirements

### MAIN MOTOR AND DRIVE SYSTEM

- Directly coupled one on one (1:1) with the elastic coupling
- Variable-speed starting with frequency converter
- High temperature protection with motor bearings (INVERSYS 55-315 Plus)

### AIR/OIL SEPARATOR

- Easy-to-detach spin-on type separator (INVERSYS 5-37 Plus)
- High-efficiency immersion type separator with long service life (INVERSYS 45-315 Plus)

### COOLING SYSTEM

- Temperature controlled fan (INVERSYS 5-30 Plus)
- Axial cooling fans controlled with secondary fan inverter (INVERSYS 30-315 Plus)



### ADDITIONAL OPTIONS TO THE GENERAL OPTIONS LIST

- Model options with Tank, without Tank, with Tank dryer (INV 5-15 Plus)

## TECHNICAL DATA

MODEL	PRESSURE		CAPACITY				MOTOR POWER kW/HP	AIR	DIMENSIONS mm			WEIGHT kg	NOISE LEVEL dB(A)
			Minimum		Maximum				Width	Length	Height		
	Bar	PSI	m <sup>3</sup> /min	SCFM	m <sup>3</sup> /min	SCFM							
INVERSYS 5 PLUS	7,5	110	0,38	11	1,03	32	5,5/7,5	1/2"	1025	650	950	235	69
	10	145	0,37	10	0,83	27							
	13	190	0,36	14	0,64	23							
INVERSYS 7 PLUS	7,5	110	0,42	14	1,40	42	7,5/10	1/2"	1025	650	950	255	70
	10	145	0,43	13	1,20	35							
	13	190	0,43	12	0,95	29							
INVERSYS 11 PLUS	7,5	110	0,77	27	1,80	64	11/15	3/4"	1175	730	1000	305	69
	10	145	0,81	29	1,61	57							
	13	190	0,74	16	1,30	46							
INVERSYS 15 PLUS	7,5	110	0,99	35	2,85	101	15/20	3/4"	1175	730	1000	345	71
	10	145	0,97	34	2,33	82							
	13	190	0,99	35	2,07	73							
INVERSYS 18 PLUS	7,5	110	1,10	37	3,50	124	18,5/25	1"	1275	850	1465	465	71
	10	145	1,00	36	3,00	106							
	13	190	1,10	38	2,60	92							
INVERSYS 22 PLUS	7,5	110	1,30	32	4,20	140	22/30	1"	1275	850	1465	500	71
	10	145	1,30	32	3,80	124							
	13	190	1,20	29	3,00	99							
INVERSYS 30 PLUS	7,5	110	1,22	43	5,30	187	30/40	1 1/4"	1575	1030	1750	695	71
	10	145	1,22	43	4,60	162							
	13	190	1,21	43	4,00	141							
INVERSYS 37 PLUS	7,5	110	1,30	46	6,80	240	37/50	1 1/4"	1575	1030	1750	715	71
	10	145	1,30	45	5,80	205							
	13	190	1,30	44	5,00	177							
INVERSYS 45 PLUS	7,5	110	1,30	46	7,60	268	45/60	1 1/4"	1575	1030	1750	945	73
	10	145	1,20	43	6,80	240							
	13	190	1,20	44	5,90	208							
INVERSYS 55 PLUS	7,5	110	2,50	88	9,90	350	55/75	1 1/2"	2000	1200	1810	1290	75
	10	145	2,40	84	8,20	290							
	13	190	2,60	91	7,40	261							
INVERSYS 75 PLUS	7,5	110	2,60	91	12,90	456	75/100	1 1/2"	2000	1200	1810	1390	77
	10	145	2,50	88	10,90	385							
	13	190	2,50	88	9,60	339							
INVERSYS 90 PLUS	7,5	110	6,20	220	16,80	593	90/125	2"	2500	1400	2037	2020	78
	10	145	6,00	213	14,40	509							
	13	190	6,20	221	12,30	434							
INVERSYS 110 PLUS	7,5	110	6,63	234	20,10	710	110/150	2"	2500	1400	2037	2380	78
	10	145	7,11	251	17,30	611							
	13	190	7,04	249	15,00	530							
INVERSYS 132 PLUS	7,5	110	6,90	244	24,30	858	132/180	2 1/2"	2750	1805	2000	2555	78
	10	145	6,80	239	20,30	717							
	13	190	9,74	344	18,10	639							
INVERSYS 160 PLUS	7,5	110	6,80	239	28,20	996	160/220	2 1/2"	2750	1805	2000	2760	78
	10	145	7,13	252	24,60	869							
	13	190	8,50	299	21,70	766							
INVERSYS 200 PLUS	7,5	110	14,03	495	37,50	1324	200/270	NW80	3250	2250	2450	4460	79
	10	145	13,90	490	32,30	1141							
	13	190	13,81	488	28,80	1017							
INVERSYS 250 PLUS	7,5	110	13,60	479	45,20	1596	250/340	NW100	3250	2250	2450	5600	79
	10	145	13,51	477	38,50	1360							
	13	190	13,50	475	33,50	1183							
INVERSYS 315 PLUS	7,5	110	13,20	466	54,10	1911	315/430	NW100	3250	2250	2450	6000	79
	10	145	13,23	467	44,30	1564							
	13	190	12,93	457	38,00	1342							

1. These values are recorded under reference conditions of 1 bar absolute air pressure, 0% relative humidity, 20 OC inlet air temperature, 71 OC thermostatic valve set value and Smartoil usage.  
DALGAKIRAN compressors reserves the right to make changes on its products without prior notice.
2. Refers to the free air flow measured in accordance with ISO 1217: 2009, Annex E standard.
3. Refers to the sound pressure level with a tolerance of  $\pm 3$  dB(A) measured in accordance with ISO 2151:2004 and ISO 9614/2 standards. For the cells consisting of two values, the second value is for 13 bar models.

DALGAKIRAN